



SSI ELITE

# SPR-610 PULSE ISOLATION RELAY

## DESCRIPTION

The SPR-610 is a 6-channel pulse isolation relay designed for high-density pulse applications where up to six RPR or SPR relays would be required. Twelve isolated solid-state Form A (K & Y) dry-contact outputs are provided, two each from four Form A inputs and one each for two Form A inputs. The SPR-610 relay contains standard-duty solid state outputs. The wetting voltage provided by the SPR-610 to the sending devices (typically electric meters) is +13 VDC. The SPR-610 may be used with meters having high or low voltage semiconductor outputs, or electro-mechanical output contacts (relays).



The SPR-610 relay's Form A inputs feature input filtering circuitry to prevent noise from false triggering the outputs. Pulses less than 18 mS are considered to be noise and will not be detected as a valid pulse. Once an input pulse, greater in length than 18 mS, is detected the corresponding outputs will be changed to match the state of the input.

Bright red and green LED indicators display the system's status at all times, thus allowing a rapid check of the system's performance without requiring any additional test equipment. The SPR-610's input and output terminal strip is a "Euro" type. When the stripped wire has been correctly installed in the terminal's slot, no conductive parts are exposed on the surface of the terminal strip, thus allowing the user maximum protection from accidental electrical shock. The "K" lead of the SPR-610's outputs are fused to prevent damage to the relays under almost any condition a user might cause such as excessive current, incorrect wiring, etc.


The SPR-610 has built-in MOV transient protection for the solid state relay contacts that eliminates the need for external protection. The SPR-610 is normally mounted inside another enclosure, suitable for the user's intended application. An optional NEMA 4X enclosure is available with the SPR-610 mounted on an internal mounting plate.

### FUNCTIONAL SUMMARY

IN	OUT
6	10
2 Wire	2 Wire
A	A

#  
TYPE  
FORM

# SPR-610



SSI ELITE

## SPR-610 PULSE ISOLATION RELAY

### SPECIFICATIONS

#### ELECTRICAL

Power Input:	120 or 208-277VAC. Burden: 10 mA at 120 VAC
Pulse Input:	Six Form A inputs. "Kin" is common return. Input has "Yin" input terminals are "pulled up" to +13VDC for pulse signal from meter.
Pulse Output:	Twelve (12) Form A dry contacts (K & Y) for energy pulses. The contacts are solid state rated at 125VAC/VDC at 100milliamps. The maximum power rating of the contacts is 800mW. Each output is factory fused at 1/10 amp. (3AG)
Contact On-State Resistance:	25 ohms maximum, 18 typical
Insulation Resistance:	50 megohms typical
Operate and Release Time:	2 to 3 milliseconds typical
Input/Output Isolation Voltage:	2500Vrms

#### MECHANICAL

Mounting:	Any position.
Size:	7.00" wide, 9.00" high, 1.8" deep
Weight:	2 pounds

#### TEMPERATURE

Temperature Range:	-38° C to +70° C, -38.4° F to +158° F
Humidity:	0 to 98% non-condensing

#### AVAILABLE OPTIONS

Input Voltages:	<ul style="list-style-type: none"><li>• 125 VDC input using the DCS-1 Power Supply.</li><li>• +15-48VDC input using the DCS-2 Power Supply</li><li>• +12VDC &amp; +24VDC/24VAC are also available</li></ul> Contact factory for other input voltages.
-----------------	---

All specifications are subject to change without notice.

# SPR-610